

安全データシート

発行日 2026/01/21

| 1. 化学品及び会社情報 | |
|--------------|--|
| 製品名 | Tungsten powder (99.9%) |
| 製品コード (製造元) | 93-7456 |
| 製品コード (販売元) | — |
| 供給者 | 富士フイルム和光純薬株式会社 大阪市中央区道修町三丁目1番2号 電話:06-6203-3741 FAX番号:06-6203-2029 |
| 緊急連絡電話番号 | 試薬営業本部西日本営業部 06-6203-3741 試薬営業本部東日本営業部 03-3270-8571 |
| 推奨用途 | 試験研究用 |
| 使用上の制限 | 推奨用途以外で使用する場合は専門家の判断を仰ぐこと。 |

2~14章

製造元SDS(翻訳・次頁以降)による。

15. 適用法令

国内法規

毒物及び劇物取締法

—

労働安全衛生法

名称等を表示すべき危険物及び有害物(法第57条)

名称等を通知すべき危険物及び有害物(法第57条の2)

労働安全衛生法 濃度基準値

| 物質名 | 8時間濃度基準値 | 短時間濃度基準値 |
|--------|----------|----------|
| 該当成分なし | — | — |

化学物質排出把握管理促進法
(PRTR法)

—

| 化学名 | CASRN | 含量 | 該当法令 |
|--------|-----------|------|--------------------------------|
| タングステン | 7440-33-7 | 100% | 安衛法 名称等を通知すべき危険物及び有害物(法第57条の2) |

16. その他の情報

引用文献および参照ホームページ等 供給者および日本法規(毒物及び劇物取締法、労働安全衛生法 法第57条の2、化学物質排出把握管理促進法(PRTR法))について本頁に記載します。
製品の詳細については次頁より製造元SDSを翻訳したものを記載します。

免責事項

和文SDSは、製造元SDSを機械翻訳したものであり、不自然な表現が含まれることがあります。

より正確な情報に関しては製造元の原文SDSでご確認願います。

記載内容は通常の実用を目的としたものであって他の物質と組み合わせるなど特殊な取扱いをする場合は使用環境に適した安全対策を実施の上ご利用ください。改訂日における最新の情報に基づいて作成されておりますが、すべての情報を網羅しているものではありませんので新たな情報を入手した場合には追加又は訂正されることがあります。また、安全な取扱い等に関する情報提供を目的としておりますので物性値や危険有害性情報などは製品規格書等とは異なりいかなる保証をなすものではありません。全ての製品にはまだ知られていない危険性を有する可能性がありますので取り扱いには十分ご注意ください。

以上

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

最終確認日 2021年7月21日

1 識別

・製品名

・商品名：タングステン粉末 (99.9%)

・品番：93-7456

・CAS番号：
7440-33-7・EC番号：
231-143-9

・安全データシートの供給者の詳細

・製造者/供給者:

Strem Chemicals, Inc.
7 マリケン・ウェイ
ニューベリーポート、マサチューセッツ州 01950
アメリカ合衆国
info@strem.com

・情報部門：技術部門

・緊急連絡先：

緊急時：ケムトレック：+1 (800) 424-9300
通常営業時間中：+1 (978) 499-1600

2 危険有害性の要約

・物質又は混合物の分類



GHS02 引火性固体

Flam. Sol. 2 H228 火気注意。可燃性固体。



GHS08 健康危害

生殖毒性 2 H361 生殖能または胎児への悪影響のおそれの疑い。



GHS07

皮膚刺激性 2 H315 皮膚刺激を引き起こす。

眼刺激 2A H319 強い眼刺激を引き起こす。

STOT SE 3 H335 呼吸器への刺激のおそれがある。

・ラベル要素

・GHSラベル要素

この単一物質は、世界調和システム（GHS）に基づき分類および表示されています。

・危険絵表示



GHS02 GHS07 GHS08

・注意喚起語 警告

(2ページに続く)

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

改訂日 2021年7月21日

商品名：タングステン粉末 (99.9%)

(1ページ続き)

・表示上の危険性決定成分：

タングステン

・危険性表示

H228 可燃性固体。

H315 皮膚刺激を引き起こす。

H319 強い眼刺激を引き起こす。

H361 生殖能または胎児への悪影響のおそれの疑い。

H335 呼吸器への刺激のおそれがある。

・注意

P210 熱、火花、裸火、熱い面から離して保管すること—禁煙

P280 保護手袋、保護衣、保護眼鏡、保護面を着用すること

P261 粉塵・煙・ガス・ミスト・蒸気・噴霧の吸入を避ける

P305+P351+P338 眼に入った場合：水で数分間注意深く洗うこと。コンタクトレンズを着用している場合は外す
容易な場合。洗浄を続ける。

P403+P233 換気のよい場所で保管すること。容器を密閉しておくこと。

P501 内容物/容器は、地方/地域/国/国際の規制に従って廃棄すること
規制に従って廃棄すること。

・分類システム：

・NFPA評価 (0~4段階)



・HMIS評価 (0~4段階評価)



・その他の危険性

・PBTおよびvPvB評価の結果

・PBT：該当なし。

・vPvB：該当なし。

3 組成及び成分情報

・化学的特性：単一物質

・CAS番号 説明

7440-33-7 タングステン

・識別番号

・EC番号：231-143-9

4 応急措置

・応急措置の説明

・一般情報：製品で汚染された衣類は直ちに除去すること。

・吸入した場合：意識不明の場合は、搬送時に患者を安定した横向きにしてください。

・皮膚に付着した場合：直ちに石鹸と水で洗い流し、十分にすすいでください。

・眼に入った場合：

目を開けた状態で流水で数分間洗い流してください。症状が続く場合は医師に相談してください。

・飲み込んだ場合：症状が続く場合は医師に相談してください。

(3ページに続く)

安全データシート
OSHA HCS (危険物安全通
信) に基づき

印刷日 2021年7月21日

2021年7月21日 改訂

商品名: タングステン粉末 (99.9%)

(2ページ続き)

- ・医師向け情報:
- ・最も重要な症状および影響 (急性および遅発性) これ以上の関連情報は入手できません。
- ・直ちに医師の診察と特別な処置が必要か否かの指示
これ以上の関連情報は入手できません。

5 火災時の措置

- ・消火剤
- ・適切な消火剤: 環境に適した火災時の措置を使用すること。
- ・単一物質または混合物に起因する特別な危険性 これ以上の関連情報は入手できません。
- ・消防士への助言
- ・保護具: 特別な措置は不要。

6 漏出時の措置

- ・人体に対する注意事項、保護具及び緊急時措置
保護具を着用すること。無防備な者を遠ざけること。
- ・環境に対する注意事項: 特別な措置は不要。
- ・封じ込め及び清掃の方法と材料:
汚染物質は項目13に従い廃棄物として処理すること。
十分な換気を確保すること。
- ・他の項目の参照
安全な取扱いに関する情報は第7節を参照してください。
保護具に関する情報は第8項を参照してください。
廃棄に関する情報はセクション13を参照してください。
- ・化学物質の防護行動基準

・PAC-1:

10 mg/m³

・PAC-2:

330 mg/m³

・PAC-3:

2,000 mg/m³

7 取扱い及び保管上の注意

- ・取扱い:
- ・安全な取扱いに関する注意事項
作業場では十分な換気・排気を確保すること。
容器の開封および取扱いには注意を払うこと。
- ・爆発・火災防止に関する情報:
着火源を遠ざける - 禁煙。
静電気から保護してください。
呼吸用保護具を用意しておくこと。
- ・安全な保管条件 (不適合物質を含む)
- ・保管:
- ・貯蔵庫及び容器が満たすべき要件: 特別な要件なし。
- ・共通保管施設における保管に関する情報: 不要。
- ・保管条件に関する追加情報: 容器を密閉して保管すること。

(4ページに続く)

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

最終確認日 2021年7月21日

商品名：タングステン粉末 (99.9%)

(3ページ続き)

・特定用途 これ以上の関連情報は入手できません。

8 ばく露防止及び保護措置

・技術システムの設計に関する追加情報：追加データなし；項目7を参照。

・管理パラメータ

・職場で監視が必要な限界値を持つ構成要素：

7440-33-7 タングステン

PEL および不溶性化合物、Weとして

REL 短時間値：10 mg/m³

長期値：5 mg/m³

Wとして

TLV 短期値: (10) mg/m³

長期的な価値: (5) NIC-3* mg/m³

としてW; * 吸入性粒子分

・追加情報：作成時に有効であったリストを使用した。

・暴露管理

・保護具：

・一般的な保護および衛生対策：

食品、飲料、飼料から遠ざけること。

汚染された衣服は直ちに脱ぐ。

休憩前および作業終了時に手を洗うこと。

保護衣類は別に保管すること。

目や皮膚への接触を避けること。

・呼吸用保護具：29 CFR 1910.134に準拠したNIOSH認定の呼吸用保護具。

・手の保護具：



保護手袋

手袋の材質は、製品／単一物質／調剤に対して不浸透性かつ耐性を持つ必要がある。

試験データが不足しているため、製品・調剤・化学混合物に対する手袋素材の推奨はできません。

化学混合物については、手袋素材に関する推奨は行えません。

浸透時間、拡散速度、および劣化を考慮した手袋素材の選択

・手袋の素材

適切な手袋の選択は、素材だけでなく、その他の品質基準や

製造者によって異なる。

・手袋素材の浸透時間

正確な貫通時間は保護手袋の製造者によって特定され、

遵守される必要があります。

・眼の保護：



密閉型ゴーグル

(5ページに続く)

安全データシート
OSHA HCS (危険物安全通
信) に基づき

印刷日 2021年7月21日

2021年7月21日 改訂

商品名: タングステン粉末 (99.9%)

(4ページ続き)

9 物理的及び化学的性質

| | |
|---|---|
| ・基本的な物理的及び化学的性質に関する情報 ・一般情報 ・性状: 物理状態: 粉末 色: 灰色 ・臭い: 無臭 ・臭い閾値: 未測定。 | |
| ・pH値: | 該当なし。 |
| ・状態変化 融点/融解範囲: | 3.410 °C (38 °F) |
| 沸点/沸騰範囲: | 5.660 °C (42 °F) |
| ・引火点: | 該当なし。 |
| ・可燃性 (固体、気体): | 火気注意。 |
| ・発火温度: | |
| 分解温度: | 未確定。 |
| ・自動点火: | 未確定。 |
| ・爆発の危険性: | 未確定。 |
| ・爆発限界: 下限: | 未確定。 |
| 上限: | 未確定。 |
| ・蒸気圧: | 該当なし。 |
| ・20 °C (68 °F) における密度: | 19.3 g/cm ³ (161.0585 lbs/gal) |
| ・20 °C (68 °F) におけるかさ密度: | 4.000 kg/m ³ |
| ・相対密度 | 未測定。 |
| ・蒸気密度 | 該当なし。 |
| ・蒸発速度 | 該当なし。 |
| ・水への溶解度/混和性 水: | 不溶。 |
| ・分配係数 (n-オクタン/水): | 未測定。 |
| ・粘度: 動粘度: | 該当なし。 |
| 動粘度: | 該当なし。 |
| ・溶剤含有量: 有機溶剤: | 0.0 % |
| 揮発性有機化合物含有量: | 0.0 g/l / 0.00 lb/gl |
| 固形分含有量: | 100.0 % |
| ・その他の情報 | これ以上の関連情報は入手できません。 |

10 安定性及び反応性

・反応性 これ以上の関連情報は入手できません。

(6ページに続く)

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

改訂日 2021年7月21日

商品名：タングステン粉末 (99.9%)

(5ページ続き)

- ・化学的安定性
- ・熱分解/避けるべき条件：仕様通りに使用すれば分解しない。
- ・危険反応の可能性 危険な反応は知られていない。
- ・避けるべき条件：これ以外の関連情報は入手できません。
- ・不適合物質：これ以外の関連情報は入手できません。
- ・危険な分解生成物：危険な分解生成物は知られていない。

11 有害性情報

- ・毒性作用に関する情報
- ・急性毒性:
- ・主な刺激作用:
- ・皮膚：皮膚および粘膜に対する刺激性。
- ・眼：刺激性。
- ・感作性：感作作用は知られていない。
- ・追加有害性情報:
- ・発がん性分類

・IARC (国際がん研究機関)

当該単一物質は未記載。

・NTP (米国国立毒性プログラム)

当該単一物質は記載されていません。

・OSHA-Ca (労働安全衛生局)

単一物質は未記載です。

12 環境影響情報

- ・毒性
- ・水生毒性：これ以上の関連情報は入手できません。
- ・残留性および分解性これ以上の関連情報は入手できません。
- ・環境システムにおける挙動:
- ・生物蓄積性これ以上の関連情報は入手できません。
- ・土壌中での移動性 これ以上の関連情報は入手できません。
- ・追加環境影響情報:
- ・一般注意事項：水に対する危険性は知られていない。
- ・PBTおよびvPvB評価の結果
- ・PBT：該当なし。
- ・vPvB：該当なし。
- ・その他の有害影響：これ以上の関連情報は入手できません。

13 廃棄上の注意

- ・廃棄物処理方法
- ・推奨事項：
家庭ごみと一緒に廃棄してはならない。製品が下水システムに流入しないようにすること。

(7ページに続く)

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

改訂日 2021年7月21日

商品名：タングステン粉末 (99.9%)

(6ページ続き)

- ・未洗浄梱包：
- ・推奨事項：公的規制に従って廃棄すること。

14 輸送上の注意

| | |
|--|--|
| <ul style="list-style-type: none"> ・国連番号 ・DOT、IMDG(海上)、IATA | UN3089 |
| <ul style="list-style-type: none"> ・国連正式品名 ・DOT ・IMDG(海上)、IATA | 金属粉末、火気注意、その他 火気注意の金属粉末、その他 |
| <ul style="list-style-type: none"> ・輸送危険有害性クラス ・DOT | |
|  | |
| <ul style="list-style-type: none"> ・クラス ・ラベル | 4 4.1 |
| <ul style="list-style-type: none"> ・IMDG(海上)、IATA(航空) | |
|  | |
| <ul style="list-style-type: none"> ・クラス ・ラベル | 4 4.1 |
| <ul style="list-style-type: none"> ・容器等級 ・DOT、IMDG(海上)、IATA(航空) | III |
| <ul style="list-style-type: none"> ・環境上の危険性： ・海洋汚染物質： | いいえ |
| <ul style="list-style-type: none"> ・使用者に対する特別な注意事項 ・分離グループ ・積載区分 ・取扱いコード ・分離コード | 該当なし。 重金属類及びその塩類（有機金属化合物を含む化合物）、粉末金属類 A H1 合理的に実行可能な範囲で乾燥状態を保持すること SG17 第5.1類の貨物から「分離して」積載すること SG25 2.1 及び 3. 類の貨物から「分離して」積載すること SG26 なお、2.1類及び3類の貨物は、コンテナ船の甲板に積載する場合、コンテナ船の甲板に積載される場合、横方向に最低2コンテナスペースの距離を保つこと。また、ローロー船に積載する場合は、6mの横方向間隔を保たなければならない。 |
| <ul style="list-style-type: none"> ・MARPOL73/78附属書II及びIBCコードに基づく ・MARPOL73/78及びIBCコードに基づくバルク輸送 | 該当なし。 |

(8ページに続く)

安全データシート
OSHA HCSに基づく

印刷日 2021年7月21日

2021年7月21日 確認済み

商品名：タングステン粉末 (99.9%)

(7ページ続き)

・輸送/追加情報：

・IMDG(海上)

・限定数量 (LQ)

5 kg

・例外数量 (EQ)

コード：E1

梱包あたりの最大正味量：30 g

梱包あたりの最大正味量：1000 g

・国連「モデル規則」：

UN 3089 金属類粉末、可燃性、その他、4.1、III

15 適用法令

・単一物質または混合物に固有の安全、健康および環境に関する規制/法令

・サラ

・第355条 (極めて危険な単一物質)：

当該単一物質は収載されていない。

・第313条 (特定有害化学物質リスト)：

当該単一物質は未収載。

・TSCA (有害物質規制法)：

当該単一物質はリストに掲載されている。

・プロポジション65

・発がん性が認められている化学物質：

単一物質は未収載です。

・女性に対する生殖毒性が確認されている化学物質：

単一物質は未収載です。

・雄の生殖毒性を引き起こすことが知られている化学物質：

未収載の単一物質です。

・発生毒性を引き起こすことが知られている化学物質：

当該単一物質は未収載。

・発がん性分類

・EPA (環境保護庁)

当該単一物質は未収載。

・TLV (ACGIHが設定した許容濃度値)

当該単一物質は未収載です

・NIOSH-Ca (米国労働安全衛生研究所)

単一物質は未収載。

・GHSラベル要素

この単一物質は、世界調和システム (GHS) に基づき分類および表示されています。

・危険性絵表示



GHS02 GHS07 GHS08

・注意喚起語 警告

(9ページに続く)

安全データシート
OSHA HCS (有害化学物質
情報システム) に基づき

印刷日 2021年7月21日

2021年7月21日 改訂

商品名: タングステン粉末 (99.9%)

(8ページ続き)

・表示上の危険性決定成分:

タングステン

・危険性表示

H228 可燃性固体。

H315 皮膚刺激を引き起こす。

H319 強い眼刺激を引き起こす。

H361 生殖能または胎児への悪影響のおそれの疑い。

H335 呼吸器への刺激のおそれがある。

・注意

P210 熱、火花、裸火、熱い面から離して保管すること—禁煙

P280 保護手袋、保護衣、保護眼鏡、保護面を着用すること

P261 粉塵・煙・ガス・ミスト・蒸気・スプレーを吸い込まないようにすること。

P305+P351+P338 眼に入った場合: 水で数分間注意深く洗うこと。コンタクトレンズを装着している場合は外す
容易な場合には外し、洗浄を続ける。

P403+P233 換気のよい場所で保管すること。容器を密閉しておくこと。

P501 内容物/容器は、地方/地域/国/国際の規制に従って廃棄すること

規制に従って廃棄すること。

・化学物質安全評価: 化学物質安全評価は実施されていません。

16 その他の情報

この情報は当社の現時点での知識に基づいています。ただし、これはいかなる保証を構成するものではありません。
特定の製品機能に関するものであり、法的効力を有する契約関係を成立させるものではありません。

・SDS発行部門: 技術部。

・連絡先: 技術部長

・作成日/最終改訂日 2021年7月21日/-

・略語・頭字語:

ADR: 欧州危険物道路運送協定 (欧州危険物道路運送に関する国際協定)

危険物の国際道路運送に関する欧州協定)

IMDG(海上): 国際海上危険物規則

DOT: 米国運輸省

IATA(航空): 国際航空運送協会

ACGIH: 米国産業衛生専門家会議

EINECS: 欧州既存商業単一物質目録

CAS: 化学抄録サービス (米国化学会の一部門)

NFPA: 米国防火協会

HMIS: 危険物識別システム (米国)

VOC: 揮発性有機化合物 (米国、EU)

PBT: 残留性、生物蓄積性及び毒性

vPvB: 超持続性・超生物蓄積性

NIOSH: 米国国立労働安全衛生研究所

OSHA: 労働安全衛生局

TLV: 許容濃度値

PEL: 許容ばく露限界

REL: 推奨ばく露限界

Flam. Sol. 2: 可燃性固体 - 区分2

皮膚刺激性 2: 皮膚腐食性/刺激性 - 区分2

眼刺激性 2A: 眼に対する重篤な損傷性/眼刺激性 - 区分2A

生殖毒性 2: 生殖毒性 - 区分2

STOT SE 3: 特定標的臓器毒性 (単回ばく露) - 区分3

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

1 Identification

- **Product name**
- **Trade name:** Tungsten powder (99.9%)
- **Item number:** 93-7456
- **CAS Number:**
7440-33-7
- **EC number:**
231-143-9
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Strem Chemicals, Inc.
7 Mulliken Way
NEWBURYPORT, MA 01950
USA
info@strem.com
- **Information department:** Technical Department
- **Emergency telephone number:**
EMERGENCY: CHEMTREC: + 1 (800) 424-9300
During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Sol. 2 H228 Flammable solid.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Warning

(Contd. on page 2)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 1)

· **Hazard-determining components of labeling:**

tungsten

· **Hazard statements**

H228 Flammable solid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 0

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7440-33-7 tungsten

· **Identification number(s)**

· **EC number:** 231-143-9

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

10 mg/m³

· **PAC-2:**

330 mg/m³

· **PAC-3:**

2,000 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 4)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7440-33-7 tungsten

PEL and insoluble compounds, as We

REL Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
as W

TLV Short-term value: (10) mg/m³
Long-term value: (5) NIC-3* mg/m³
as W; * respirable fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:** A NIOSH approved respirator in accordance with 29 CFR 1910.134.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Powder
 · **Color:** Grey
 · **Odor:** Odorless
 · **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

· **Melting point/Melting range:** 3.410 °C (38 °F)
 · **Boiling point/Boiling range:** 5.660 °C (42 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Flammable.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Not determined.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· **Lower:** Not determined.
 · **Upper:** Not determined.

· **Vapor pressure:** Not applicable.

· **Density at 20 °C (68 °F):** 19.3 g/cm³ (161.0585 lbs/gal)

· **Bulk density at 20 °C (68 °F):** 4.000 kg/m³

· **Relative density** Not determined.

· **Vapor density** Not applicable.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

· **Water:** Insoluble.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **Dynamic:** Not applicable.
 · **Kinematic:** Not applicable.

· **Solvent content:**

· **Organic solvents:** 0.0 %
 · **VOC content:** 0.0 g/l / 0.00 lb/gl

· **Solids content:** 100.0 %

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 6)

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 5)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

Substance is not listed.

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021



Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|--|---|
| · UN-Number · DOT, IMDG, IATA | UN3089 |
| · UN proper shipping name · DOT · IMDG, IATA | Metal powders, flammable, n.o.s. METAL POWDER, FLAMMABLE, N.O.S. |
| · Transport hazard class(es) · DOT | |
|  | |
| · Class · Label | 4 4.1 |
| · IMDG, IATA | |
|  | |
| · Class · Label | 4 4.1 |
| · Packing group · DOT, IMDG, IATA | III |
| · Environmental hazards: · Marine pollutant: | No |
| · Special precautions for user · Segregation groups | Not applicable. Heavy metals and their salts (including their organometallic compounds), powdered metals |
| · Stowage Category · Handling Code · Segregation Code | A H1 Keep as dry as reasonably practicable SG17 Stow "separated from" class 5.1 SG25 Stow "separated from" goods of classes 2.1 and 3. SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 8)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 7)

· Transport/Additional information:

· IMDG

· **Limited quantities (LQ)**

5 kg

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

· **UN "Model Regulation":**

UN 3089 METAL POWDERS, FLAMMABLE, N.O.S., 4.1, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

Substance is not listed.

· **TLV (Threshold Limit Value established by ACGIH)**

Substance is not listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Warning

(Contd. on page 9)

Safety Data Sheet
according to OSHA HCS

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Tungsten powder (99.9%)

(Contd. of page 8)

· **Hazard-determining components of labeling:**

tungsten

· **Hazard statements**

H228 Flammable solid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Technical Department.

· **Contact:** Technical Director

· **Date of preparation / last revision** 07/21/2021 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Sol. 2: Flammable solids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3