

SAFETY DATA SHEET

According to JIS Z 7253:2019

Issue Date 14-Apr-2025

Revision Number 3.06

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	2-Methoxyethyl Acetate
Product Code	017-10582,011-10585

Supplier	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-2029
Emergency telephone number	+81-6-6203-3741 / +81-3-3270-8571
Recommended uses	For research use only
Restrictions on use	Seek expert judgment when using for purposes other than those recommended.

Section 2: HAZARDS IDENTIFICATION

GHS classification

Classification of the substance or mixture

Flammable liquids

Serious eye damage/eye irritation

Reproductive Toxicity

Specific target organ toxicity (single exposure)

Category 1 central nervous system, blood system, kidneys

Category 3 Narcotic effects

Specific target organ toxicity (repeated exposure)

Category 1 blood system, testes

Acute aquatic toxicity

Chronic aquatic toxicity

Category 3

Category 2B

Category 1A

Category 1, Category 3

Category 1

Category 3

Category 2

Pictograms



Signal word

Danger

Hazard statements

H226 - Flammable liquid and vapour

H320 - Causes eye irritation

H360 - May damage fertility or the unborn child

H336 - May cause drowsiness or dizziness

H402 - Harmful to aquatic life

H411 - Toxic to aquatic life with long lasting effects

H370 - Causes damage to the following organs: central nervous system, blood system, kidneys

H372 - Causes damage to the following organs through prolonged or repeated exposure: blood system, testes

Precautionary statements-(Prevention)

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required

- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary statements-(Response)

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use suitable extinguishing media for extinction
- Collect spillage

Precautionary statements-(Storage)

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Precautionary statements-(Disposal)

- Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Substance

Formula CH₃COOCH₂CH₂OCH₃

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
2-Methoxyethyl Acetate	98.0	118.13	(2)-740	*	110-49-6

Note on ISHL No.: * in the table means announced chemical substances.

Section 4: FIRST AID MEASURES

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

Special extinguishing method

No information available

Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminant and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recovery, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling

Technical measures

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with local exhaust ventilation. Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging. Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle. In places other than those specified, should not be smoking or eating and drinking. Should not be brought contaminated protective equipment and gloves to rest stops. Deny unnecessary entry of non-emergency personnel to the handling area.

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Storage

Safe storage conditions

Storage conditions

Keep container protect from light, store in well-ventilated place at room temperature (preferably cool). Keep container tightly closed.

Safe packaging material

Glass

Incompatible substances

Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

Exposure limits

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
2-Methoxyethyl Acetate 110-49-6	TWA: 0.1 ppm OEL TWA: 0.48 mg/m ³ OEL Skin	N/A	TWA: 0.1 ppm Skin

Chemical Name	Concentration standard value set by the Minister of Health, Labor and Welfare (8hr)	Concentration standard value set by the Minister of Health, Labor and Welfare (Short-Term)
2-Methoxyethyl Acetate 110-49-6	1 ppm	N/A

Personal protective equipment

Respiratory protection gas mask for organic gas (JIS T 8152)
Hand protection chemical protective gloves (JIS T 8116)
Eye protection protective eyeglasses or chemical safety goggles (JIS T 8147)
Skin and body protection Long-sleeved work clothes

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

If this product is classified as "Chemical Substances Hazardous to Skin, etc.", use appropriate protective equipment to them.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form

Color Colorless - nearly colorless
Turbidity clear
Appearance liquid

Odor

Melting point/freezing point

- 65 °C

Boiling point, initial boiling point and boiling range

145 °C

Flammability

Flammable liquid and vapor

Evaporation rate:

no data available

Flammability (solid, gas):

no data available

Upper/lower flammability or explosive limits

Upper:

12.3 vol%

Lower:

1.5 vol%

Flash point

40 °C / 104 °F

Auto-ignition temperature:

380 °C / 738 °F

Decomposition temperature:

no data available

pH

no data available

Viscosity (coefficient of viscosity)

no data available

Dynamic viscosity

no data available

Solubilities

water , Ethanol and acetone : Very soluble.

n-Octanol/water partition coefficient:(log Pow)

0.121

Vapour pressure

0.44 kPa (20 °C)

Specific Gravity / Relative density

1.004 - 1.010 g/mL

Vapour density

4.1

Particle characteristics

no data available

Section 10: STABILITY AND REACTIVITY

Stability

Reactivity no data available
Chemical stability May be altered by light.

Hazardous reactions

The substance decomposes on burning producing toxic or corrosive gases and fumes. Reacts violently with acids, may cause fire or explosion. Reacts violently with bases.

Conditions to avoid

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Carbon monoxide (CO), Carbon dioxide (CO₂)

Section 11: TOXICOLOGICAL INFORMATION

*NITE: National Institute of Technology and Evaluation (JAPAN)

https://www.chem-info.nite.go.jp/en/chem/chrip/chrip_search/srhInput

Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Methoxyethyl Acetate	2,900 mg/kg (Rat)	5,214 mg/kg (Rabbit)	N/A

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas- source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust- source information	Acute toxicity -inhalation mist- source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.		Based on the NITE GHS classification results.

Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Carcinogenicity

Chemical Name	Carcinogenicity source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Reproductive toxicity

Chemical Name	Reproductive toxicity source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

STOT-single exposure

Chemical Name	STOT -single exposure- source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Aspiration hazard

Chemical Name	Aspiration Hazard source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.

Section 12: ECOLOGICAL INFORMATION

*NITE: National Institute of Technology and Evaluation (JAPAN)
https://www.chem-info.nite.go.jp/en/chem/chrip/chrip_search/srhInput

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Methoxyethyl Acetate	N/A	LC50 : <i>M.beryllina</i> = 40 mg/L 96h	EC10 : <i>Ceriodaphnia affinis</i> 0.06 mg/L 7days

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
2-Methoxyethyl Acetate	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Persistence and degradability	No information available
Bioaccumulative potential	No information available
Mobility in soil	No information available
Hazard to the ozone layer	No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

ADR/RID

UN number	UN1189
Proper shipping name:	Ethylene glycol monomethyl ether acetate
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant	Yes

IMDG

UN number	UN1189
Proper shipping name:	Ethylene glycol monomethyl ether acetate
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant (Sea)	Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

IATA

UN number	UN1189
Proper shipping name:	Ethylene glycol monomethyl ether acetate
UN classification	3
Subsidiary hazard class	
Packing group	III
Environmentally Hazardous Substance	Yes

Section 15: REGULATORY INFORMATION

Japanese regulations

Fire Service Act	Category IV, Class II petroleum, dangerous grade 3 water-soluble
Poisonous and Deleterious Substances Control Law	Not applicable
Industrial Safety and Health Act	Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57) Notifiable Substances (Law Art.57-2) Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1 Item 4) Chemical Substances Hazardous to Skin, etc.(Regulations Article 594-2 Paragraph 1)
Regulations for the carriage and storage of dangerous goods in ship	Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
Civil Aeronautics Law	Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
Marine Pollution Prevention Law	Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y
Pollutant Release and Transfer Register Law (2023.4.1-)	Class 1
Class 1 - No.	135
Air Pollution Control Law	Hazardous Air Pollutants

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2)	Pollutant Release and Transfer Register Law (2023.4.1-)
2-Methoxyethyl Acetate 110-49-6 (98.0)	-	Applicable	Applicable

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)
https://www.chem-info.nite.go.jp/en/chem/chrip/chrip_search/srhInput
 IATA dangerous Goods Regulations
 RTECS:Registry of Toxic Effects of Chemical Substances
 Japan Industrial Safety and Health Association GHS Model SDS
 Dictionary of Synthetic Organic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.
 Chemical Dictionary, Kyouritsu Publishing Co., Ltd.
 etc

Record of SDS revisions

The following contents were revised. Fire fighting measures. Exposure controls/personal protection. Stability and reactivity. Toxicological information. Ecological information. Regulatory information.

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z 7252:2019. *JIS: Japanese Industrial Standards

End of Safety Data Sheet