

SAFETY DATA SHEET

According to JIS Z 7253:2019
Revision date 22-Dec-2022
 Revision Number 3.03

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	1,2-Epoxybutane
Product Code	026-05423,020-05426

Manufacturer	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-5964
Supplier	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-2029
Emergency telephone number	+81-6-6203-3741 / +81-3-3270-8571
Recommended uses and restrictions on use	For research use only

Section 2: HAZARDS IDENTIFICATION

GHS classification

Classification of the substance or mixture

Self-reactive substances and mixtures

Flammable liquids

Acute toxicity - Oral

Acute toxicity - Dermal

Acute toxicity - Inhalation (Vapors)

Skin corrosion/irritation

Serious eye damage/eye irritation

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single exposure)

Category 3 Respiratory irritation, Narcotic effects

Specific target organ toxicity (repeated exposure)

Category 2 respiratory system

Acute aquatic toxicity

Type G

Category 2

Category 4

Category 4

Category 3

Category 1

Category 1

Category 2

Category 2

Category 3

Category 2

Category 3

Pictograms



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H331 - Toxic if inhaled
 H341 - Suspected of causing genetic defects
 H351 - Suspected of causing cancer
 H335 - May cause respiratory irritation
 H336 - May cause drowsiness or dizziness
 H402 - Harmful to aquatic life
 H373 - May cause damage to the following organs through prolonged or repeated exposure: respiratory system

Precautionary statements-(Prevention)

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Do not eat, drink or smoke when using this product
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary statements-(Response)

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Call a POISON CENTER or doctor/physician if you feel unwell
- Wash contaminated clothing before reuse
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth
- Do NOT induce vomiting
- In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary statements-(Storage)

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up

Precautionary statements-(Disposal)

- Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Substance

Formula C₄H₈O

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
1,2-Epoxybutane	95.0	72.11	(2)-229	*	106-88-7

Note on ISHL No.: * in the table means announced chemical substances.

Impurities and/or Additives: Not applicable

Section 4: FIRST AID MEASURES**Inhalation**

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

Special extinguishing method

No information available

Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminant and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recovery, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling**Technical measures**

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle In places other than those specified, should not be smoking or eating and drinking Should not be brought contaminated protective equipment and gloves to rest stops Deny unnecessary entry of non-emergency personnel to the handling area

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Storage**Safe storage conditions****Storage conditions**

Keep container protect from light, store in well-ventilated place at room temperature (preferably cool). Keep container tightly closed.

Safe packaging material

Glass

Incompatible substances

Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Engineering controls**

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

Exposure limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Personal protective equipment**Respiratory protection**

gas mask for organic gas

Hand protection

Impermeable protective gloves

Eye protection

protective eyeglasses or chemical safety goggles

Skin and body protection

Long-sleeved work clothes

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**Form****Color**

Colorless - slightly yellow

Turbidity

clear

Appearance

liquid

Odor

characteristic odor

Melting point/freezing point

no data available

Boiling point, initial boiling point and boiling range

63 °C

Flammability

Highly flammable liquid and vapor

Evaporation rate:

no data available

Flammability (solid, gas):

no data available

Upper/lower flammability or explosive limits**Upper:**

20 vol%

Lower:

1.5vol%

Flash point

-26 °C

Auto-ignition temperature:

439 °C

Decomposition temperature:

no data available

pH

no data available

Viscosity (coefficient of viscosity)

no data available

Dynamic viscosity

no data available

Solubilities

Ethanol and acetone : Very soluble. water : soluble .

n-Octanol/water partition coefficient:(log Pow)

0.416

Vapour pressure

no data available

Specific Gravity / Relative density

0.827 -0.834 g/m L (20 °C)

Vapour density

no data available

Particle characteristics

no data available

Section 10: STABILITY AND REACTIVITY**Stability****Reactivity**

no data available

Chemical stability

May be altered by light.

Hazardous reactions

None under normal processing

Conditions to avoid

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition productsCarbon monoxide (CO), Carbon dioxide (CO₂)**Section 11: TOXICOLOGICAL INFORMATION****Acute toxicity**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-Epoxybutane	500 mg/kg (Rat)	1469 mg/kg (Rabbit)	> 6.3 mg/L (Rat) 4 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas- source information
1,2-Epoxybutane	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust- source information	Acute toxicity -inhalation mist- source information
1,2-Epoxybutane	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Carcinogenicity

Chemical Name	Carcinogenicity source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Chemical Name	NTP	IARC	ACGIH	JSOH (Japan)
1,2-Epoxybutane 106-88-7	-	Group 2B	-	Group 2B

Reproductive toxicity

Chemical Name	Reproductive toxicity source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

STOT-single exposure

Chemical Name	STOT -single exposure- source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Aspiration hazard

Chemical Name	Aspiration Hazard source information
1,2-Epoxybutane	Based on the NITE GHS classification results.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
1,2-Epoxybutane	EC50: <i>Desmodesmus subspicatus</i> 500 mg/L 72 h	LC50: <i>Leuciscus idus</i> 100 - 220 mg/L 96 h	EC50 : <i>Daphnia magna</i> 69.8 mg/L 48 h

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
1,2-Epoxybutane	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Persistence and degradability	Readily biodegradable
Bioaccumulative potential	No information available
Mobility in soil	No information available
Hazard to the ozone layer	No information available

Section 13: DISPOSAL CONSIDERATIONS**Waste from residues**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION**ADR/RID**

UN number	UN3022
Proper shipping name:	1,2-Butylene oxide, stabilized
UN classification	3
Subsidiary hazard class	
Packing group	II
Marine pollutant	Not applicable

IMDG

UN number	UN3022
Proper shipping name:	1,2-Butylene oxide, stabilized
UN classification	3
Subsidiary hazard class	
Packing group	II
Marine pollutant (Sea)	Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

IATA

UN number	UN3022
Proper shipping name:	1,2-Butylene oxide, stabilized
UN classification	3
Subsidiary hazard class	
Packing group	II
Environmentally Hazardous Substance	Not applicable

Section 15: REGULATORY INFORMATION**International Inventories**

EINECS/ELINCS	Listed
TSCA	Listed

Japanese regulations

Fire Service Act	Category IV, Class I petroleum, dangerous grade 2
Poisonous and Deleterious Substances Control Law	Not applicable
Industrial Safety and Health Act	Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18) Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)No.193 Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1 Item 4)
Regulations for the carriage and storage of dangerous goods in ship	Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
Civil Aeronautics Law	Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
Marine Pollution Prevention Law	Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y
Pollutant Release and Transfer Register Law (~2023.3.31)	Class 1
Class 1 - No.	66
Pollutant Release and Transfer Register Law (2023/4/1~)	Class 1
Class 1 - No.	66
Export Trade Control Order	Not applicable
Air Pollution Control Law	Hazardous Air Pollutants

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2) (~2024.3.31)	Pollutant Release and Transfer Register Law (~2023.3.31)
1,2-Epoxybutane 106-88-7 (95.0)	-	Applicable	Applicable

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)
<http://www.safe.nite.go.jp/japan/db.html>
 IATA dangerous Goods Regulations
 RTECS:Registry of Toxic Effects of Chemical Substances
 Japan Industrial Safety and Health Association GHS Model SDS
 Dictionary of Synthetic Organic Chemistry, SSOCJ, Koudansha Scientific Co.Ltd.
 Chemical Dictionary, Kyouritsu Publishing Co., Ltd.
 etc

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z7252(2019). *JIS: Japanese Industrial Standards

End of Safety Data Sheet