



SAFETY DATA SHEET

According to JIS Z 7253:2019

Revision date 14-Feb-2023

Revision Number 3.03

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	2-Methylbutane		
Product Code	168-09195		
Manufacturer	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-5964		
Supplier Emergency telephone number	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-2029 +81-6-6203-3741 / +81-3-3270-8571		
Recommended uses and	For research use only		

Section 2: HAZARDS IDENTIFICATION

GHS classification

restrictions on use

Classification of the substance or mixture

Flammable liquids

Serious eye damage/eye irritation

Specific target organ toxicity (single exposure)

Category 3

Category 3

Respiratory irritation, Narcotic effects

Specific target organ toxicity (repeated exposure)

Aspiration hazard

Acute aquatic toxicity

Category 1

Category 2

Pictograms



Hazard statements

H224 - Extremely flammable liquid and vapor

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H304 - May be fatal if swallowed and enters airways

H401 - Toxic to aquatic life

Precautionary statements-(Prevention)

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- · Do not eat, drink or smoke when using this product

- · Use only outdoors or in a well-ventilated area
- · Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- · Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- · Take precautionary measures against static discharge
- · Keep cool

Precautionary statements-(Response)

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- · Do NOT induce vomiting
- In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary statements-(Storage)

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Precautionary statements-(Disposal)

• Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Substance

Formula (CH3)2CHCH2CH3

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
2-Methylbutane	97.0	72.15	(2)-5	公表	78-78-4

Note on ISHL No.: * in the table means announced chemical substances.

Impurities and/or Additives: Not applicable

Section 4: FIRST AID MEASURES

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog), Carbon dioxide (CO2), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

Special extinguishing method

No information available

Special protective actions for

fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminent and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recoverly, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling

Technical measures

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle In places other than those specified, should not be smoking or eating and drinking Should not be brought contaminated protective equipment and gloves to rest stops Deny unnecessary entry of non-emergency personnel to the handling area

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Storage

Safe storage conditions

Storage conditions Keep container protect from light, store

in well-ventilated place at room temperature (preferably cool). Keep container tightly

closed.

Safe packaging material

Glass

Incompatible substances Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and handand eye-wash facility. And display their position clearly.

Exposure limits

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
2-Methylbutane	N/A	N/A	TWA: 1000 ppm
78-78-4			

Personal protective equipment

Respiratory protection gas mask for organic gas
Hand protection Impermeable protective gloves

Eye protection protective eyeglasses or chemical safety goggles

Skin and body protection Long-sleeved work clothes

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form

ColorcolorlessTurbidityclearAppearanceliquid

Odorcharacteristic odorMelting point/freezing pointno data available

Boiling point, initial boiling point and boiling range 30 °C

Flammability Extremely flammable liquid and vapor

Evaporation rate: no data available Flammability (solid, gas): no data available

Upper/lower flammability or

explosive limits

Upper: 7.6vol% Lower: 1.4vol% Flash point <-51 °C Auto-ignition temperature: 420 °C

Decomposition temperature:no data availablepHno data availableViscosity (coefficient of viscosity)no data available

Dynamic viscosity no data available

Solubilities Ethanol and acetone: Very soluble, water: practically

insoluble, or insoluble.

n-Octanol/water partition coefficient:(log Pow)

Vapour pressureno data availableSpecific Gravity / Relative density0.617-0.623g/mLVapour densityno data availableParticle characteristicsno data available

Section 10: STABILITY AND REACTIVITY

2.3

Stability

Reactivity no data available
Chemical stability May be altered by light.

Hazardous reactions

None under normal processing

Conditions to avoid

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Carbon monooxide (CO), Carbon dioxide (CO2)

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50 N/A	Dermal LD50 N/A	Inhalation LC50 280000 mg/m³ (Rat) 4 h		
	N/A	280000 mg/m ³ (Rat) 4 h		
Acute toxicity -oral- source	Acute toxicity -dermal- source information			
2-Methylbutane Based on the NITE GHS		source information		
Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.		
classification results.	classification results.	classification results.		
Acute toxicity -inhalation	Acute toxicity -inhalation dust-	Acute toxicity -inhalation mi		
		source information		
Based on the NITE GHS	Based on the NITE GHS	Based on the NITE GHS		
classification results.	classification results.	classification results.		
		tion source information		
hylbutane	Based on the NITE GHS classit	fication results.		
Chemical Name		Serious eye damage/irritation source information		
2-Methylbutane		fication results.		
on				
Chemical Name		Respiratory or Skin sensitization source information		
2-Methylbutane		Based on the NITE GHS classification results.		
у				
ical Name	germ cell mutagencity source information			
hylbutane	Based on the NITE GHS classification results.			
	•			
ical Name	Carcinogenicity source information			
hylbutane	Based on the NITE GHS classification results.			
	<u> </u>			
ical Name	Reproductive toxicity source information			
hylbutane	Based on the NITE GHS classification results.			
-	•			
STOT-single exposure Chemical Name		STOT -single exposure- source information		
2-Methylbutane		Based on the NITE GHS classification results.		
•	•			
STOT-repeated exposure Chemical Name		STOT -repeated exposure- source information		
2-Methylbutane		Based on the NITE GHS classification results.		
-	-			
Aspiration hazard Chemical Name		Aspiration Hazard source information		
2-Methylbutane		Based on the NITE GHS classification results.		
	ical Name hylbutane ical Name hylbutane ical Name hylbutane on ical Name hylbutane y ical Name hylbutane	vapor- source information Based on the NITE GHS Classification results.		

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Methylbutane	N/A	N/A	EC50:Daphnia magna
			2.3 mg/L 48 h

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
,		Based on the NITE GHS classification results.

Persistence and degradability
Bioaccumulative potential
Mobility in soil

No information available
No information available
No information available

Hazard to the ozone layer

Mobility

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

ADR/RID

UN number UN1265 Proper shipping name: **Pentanes**

UN classfication 3 Subsidiary hazard class

Packing group

Marine pollutant Not applicable

IMDG

UN1265 **UN** number Proper shipping name: **Pentanes**

UN classfication Subsidiary hazard class

Packing group

Marine pollutant (Sea) Not applicable

Transport in bulk according to No information available

Annex II of MARPOL 73/78 and

the IBC Code

IATA

UN1265 **UN** number Proper shipping name: Pentanes

UN classfication Subsidiary hazard class Packing group

Environmentally Hazardous

Substance

Not applicable

Section 15: REGULATORY INFORMATION

International Inventories

Listed **EINECS/ELINCS TSCA** Listed

Japanese regulations

Fire Service Act Category IV, special inflammable materials, dangerous grade 1 Not applicable

Poisonous and Deleterious

Substances Control Law

Industrial Safety and Health Act Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57,

Para.1, Enforcement Order Art.18)

Notifiable Substances (Law Art.57-2, Enforcement Oder Art.18-2 Attached Table

No.9)No.543

Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1

Item 4)

Regulations for the carriage and storage of dangerous

Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding

Transport by Ship and Storage, Attached Table 1)

goods in ship

Civil Aeronautics Law Flammable Liquids (Ordinance Art.194, MITL Nortification for Air Transportation of

Explosives etc., Attached Table 1)

Pollutant Release and Transfer Not applicable

Register Law (~2023.3.31)

Pollutant Release and Transfer

Register Law (2023/4/1~)

Not applicable

Export Trade Control Order Not applicable

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2) (~2024.3.31)	Pollutant Release and Transfer Register Law (~2023.3.31)
2-Methylbutane	-	Applicable	-
78-78-4 (97.0)			

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)

http://www.safe.nite.go.jp/japan/db.html IATA dangerous Goods Regulations

RTECS:Registry of Toxic Effects of Chemical Substances Japan Industrial Safety and Health Association GHS Model SDS

Dictionary of Synthetic Oraganic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.

Chemical Dictionary, Kyouritsu Publishing Co., Ltd.

etc

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z7252(2019). *JIS: Japanese Industrial Standards

End of Safety Data Sheet