

SAFETY DATA SHEET

According to JIS Z 7253:2019
Revision Date 28-Sep-2021
 Version 3.02

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product name	Styrene Monomer
Product code	199-08207,191-08206

Manufacturer	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-5964
Supplier	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-2029
Emergency telephone number	+81-6-6203-3741 / +81-3-3270-8571
Recommended uses and restrictions on use	For research use only

Section 2: HAZARDS IDENTIFICATION

GHS classification

Classification of the substance or mixture

Flammable liquids	Category 3
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1, Category 3
Category 1 central nervous system	
Category 3 Respiratory tract irritation, Narcotic effects	
Specific target organ toxicity (repeated exposure)	Category 1
Category 1 nervous system, Olfactory organ, Visual organ, respiratory system, liver	
Aspiration hazard	Category 1
Short-term (acute) hazardous to the aquatic environment	Category 1
Long-term (chronic) hazardous to the aquatic environment	Category 2

Pictograms



Signal word

Danger

Hazard statements

- H226 - Flammable liquid and vapor
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H341 - Suspected of causing genetic defects

H350 - May cause cancer
 H360 - May damage fertility or the unborn child
 H335 - May cause respiratory irritation
 H336 - May cause drowsiness or dizziness
 H304 - May be fatal if swallowed and enters airways
 H400 - Very toxic to aquatic life
 H411 - Toxic to aquatic life with long lasting effects
 H370 - Causes damage to the following organs: central nervous system
 H372 - Causes damage to the following organs through prolonged or repeated exposure: nervous system, Olfactory organ, Visual organ, respiratory system, liver

Precautionary statements-(Prevention)

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required.
- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Avoid release to the environment
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary statements-(Response)

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Wash contaminated clothing before reuse.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting.
- In case of fire: Use CO2, dry chemical, or foam for extinction
- Collect spillage

Precautionary statements-(Storage)

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed

Precautionary statements-(Disposal)

- Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Substance

Formula C6H5CH:CH2

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
Styrene	99.0	104.15	(3)-4	公表	100-42-5

Impurities and/or Additives : Stabilizer : p-t-Butylcatechol abt. 0.003%

Section 4: FIRST AID MEASURES

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog), Carbon dioxide (CO₂), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

Special extinguishing method

No information available

Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminant and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recovery, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling**Technical measures**

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging. Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle. In places other than those specified, should not be smoking or eating and drinking. Should not be brought contaminated protective equipment and gloves to rest stops. Deny unnecessary entry of non-emergency personnel to the handling area.

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Storage**Safe storage conditions****Storage conditions**

Keep container protect from light tightly closed. Store in a cool (2-10 °C) place.

Safe packaging material

Glass, Iron

Incompatible substances

Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

Exposure limits

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
Styrene 100-42-5	TWA: 20 ppm OEL TWA: 85 mg/m ³ OEL Skin ISHL/ACL: 20 ppm	ISHL/ACL: 20 ppm	STEL: 40 ppm TWA: 20 ppm

Personal protective equipment**Respiratory protection**

gas mask for organic gas

Hand protection

Impermeable protective gloves

Eye protection

protective eyeglasses or chemical safety goggles

Skin and body protection

Long-sleeved work clothes

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form**Color**

colorless

Turbidity

clear

Appearance

liquid

Odor

No data available

Melting point/freezing point

-31 °C

Boiling point, initial boiling point and boiling range

145 °C

Flammability

Flammable liquid and vapor

Evaporation rate:

No data available

Flammability (solid, gas):

No data available

Upper/lower flammability or explosive limits**Upper :**

6.1 vol%

Lower :

1.1 vol%

Flash point

31 °C

Auto-ignition temperature:

490 °C

Decomposition temperature:

No data available

pH

No data available

Viscosity (coefficient of viscosity)

No data available

Dynamic viscosity

No data available

Solubilities

Ethanol , acetone : Very soluble. water : practically insoluble, or insoluble .

n-Octanol/water partition coefficient:(log Pow)

3.2

Vapour pressure

670 Pa

Specific Gravity / Relative density

0.902-0.910g/mL

Vapour density

3.6 (air = 1)

Particle characteristics

No data available

Section 10: STABILITY AND REACTIVITY

Stability

Reactivity No data available
Chemical stability May be altered by light.

Hazardous reactions

None under normal processing

Conditions to avoid

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Carbon monoxide (CO), Carbon dioxide (CO₂)

Section 11: TOXICOLOGICAL INFORMATION
--

Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene	2650 mg/kg (Rat)	N/A	2,770 ppm (Rat) 4 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas- source information
Styrene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust- source information	Acute toxicity -inhalation mist- source information
Styrene	Based on the NITE GHS Classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
Styrene	Based on the NITE GHS classification results.

Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
Styrene	Based on the NITE GHS classification results.

Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
Styrene	Based on the NITE GHS classification results.

Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
Styrene	Based on the NITE GHS classification results.

Carcinogenicity

Chemical Name	Carcinogenicity source information
Styrene	Based on the NITE GHS classification results.

Chemical Name	NTP	IARC	ACGIH	JSOH (Japan)
Styrene 100-42-5	R	2B	-	Group 2B

Reproductive toxicity

Chemical Name	Reproductive toxicity source information
Styrene	Based on the NITE GHS classification results.

STOT-single exposure

Chemical Name	STOT -single exposure- source information
Styrene	Based on the NITE GHS classification results.

STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information
Styrene	Based on the NITE GHS classification results.

Aspiration hazard

Chemical Name	Aspiration Hazard source information
Styrene	Based on the NITE GHS classification results.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Styrene	<i>EC50:Pseudokirchneriella subcapitata</i> 0.15 - 3.2 mg/L 96 h static <i>EC50:Pseudokirchneriella subcapitata</i> 0.46 - 4.3 mg/L 72 h static <i>EC50:Pseudokirchneriella subcapitata</i> 0.72 mg/L 96 h <i>EC50:Pseudokirchneriella subcapitata</i> 1.4 mg/L 72 h	<i>LC50: Fathead minnow</i> 4.02 mg/L 96 h	<i>EC50:Daphnia magna</i> 3.3 - 7.4 mg/L 48 h

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
Styrene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Persistence and degradability	No information available
Bioaccumulative potential	No information available
Mobility in soil	No information available
Hazard to the ozone layer	No information available
Mobility	

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

ADR/RID

UN number	UN2055
Proper shipping name:	Styrene monomer, stabilized
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant	Yes

IMDG

UN number	UN2055
Proper shipping name:	Styrene monomer, stabilized
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant (Sea)	Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

IATA

UN number UN2055
Proper shipping name: Styrene monomer, stabilized
UN classification 3
Subsidiary hazard class
Packing group III
Environmentally Hazardous Substance Yes

Section 15: REGULATORY INFORMATION

International Inventories

EINECS/ELINCS Listed
TSCA Listed

Japanese regulations

Fire Service Act Category IV, Class II petroleum, dangerous grade 3
Poisonous and Deleterious Substances Control Law Not applicable
Industrial Safety and Health Act Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18)
 Group 2 Specified Chemical Substance
 Substances with Health Hazards Prevention Guideline(Carcinogenicity Substance)
 Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)No.323
Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc Priority Assessment Chemical Substances (Law Article 2, Para.5)
Regulations for the carriage and storage of dangerous goods in ship Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
Civil Aeronautics Law Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
Marine Pollution Prevention Law Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y
Pollutant Release and Transfer Register Law Class 1
Class 1 - No. 240
Water Pollution Control Act Specified substances(Law Art.2 Para.4, Enforcement Order Art.3-3)
Export Trade Control Order Not applicable
Air Pollution Control Law Hazardous Air Pollutants
Offensive Odor Control Law Specified Offensive Odor Substances

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2)	Pollutant Release and Transfer Register Law
Styrene 100-42-5 (99.0)	-	Applicable	Applicable

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)
<http://www.safe.nite.go.jp/japan/db.html>
 IATA dangerous Goods Regulations
 RTECS:Registry of Toxic Effects of Chemical Substances
 Japan Industrial Safety and Health Association GHS Model SDS
 Dictionary of Synthetic Organic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.
 Chemical Dictionary, Kyouritsu Publishing Co., Ltd.
 etc

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z7252(2019). *JIS: Japanese Industrial Standards

End of Safety Data Sheet