



# SAFETY DATA SHEET

According to JIS Z 7253:2019

Revision date 27-Feb-2024

Revision Number 1.08

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	Wetting Tension Test Mixture No.30.0
Product Code	232-01821

**Supplier** FUJIFILM Wako Pure Chemical Corporation

1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan

Phone: +81-6-6203-3741 Fax: +81-6-6203-2029

Emergency telephone number +81-6-6203-3741 / +81-3-3270-8571

**Recommended uses** For research use only

**Restrictions on use**Seek expert judgment when using for purposes other than those recommended.

## **Section 2: HAZARDS IDENTIFICATION**

**GHS** classification

Classification of the substance or mixture

Flammable liquids
Category 3
Acute toxicity - Inhalation (Vapors)
Category 4
Serious eye damage/eye irritation
Category 2B
Reproductive Toxicity
Category 1B
Specific target organ toxicity (single exposure)
Category 1

Category 1 central nervous system, blood system, kidneys, liver

Specific target organ toxicity (repeated exposure) Category 1

Category 1 blood system, testes

## **Pictograms**



Signal word

Danger

## Hazard statements

- H226 Flammable liquid and vapour
- H320 Causes eye irritation
- H332 Harmful if inhaled
- H360 May damage fertility or the unborn child
- H370 Causes damage to the following organs: central nervous system, blood system, kidneys, liver
- H372 Causes damage to the following organs through prolonged or repeated exposure: blood system, testes

## **Precautionary statements-(Prevention)**

- · Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Use only outdoors or in a well-ventilated area
- · Wash face, hands and any exposed skin thoroughly after handling
- · Do not breathe dust/fume/gas/mist/vapors/spray
- · Do not eat, drink or smoke when using this product

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- · Keep container tightly closed
- · Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- · Use only non-sparking tools
- Take precautionary measures against static discharge

## Precautionary statements-(Response)

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use suitable extinguishing media for extinction

#### Precautionary statements-(Storage)

- · Store locked up
- · Store in a well-ventilated place. Keep cool

#### **Precautionary statements-(Disposal)**

Dispose of contents/container to an approved waste disposal plant

**Others** 

Other hazards Not available

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Mixture

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
2-Ethoxyethanol	<100	90.12	(2)-2424,(2)-411,(7) -97	*	110-80-5

Note on ISHL No.: \* in the table means announced chemical substances.

**Substances Remarks:** This Product includes the following componets. COLORANT; < 0.1 %

## **Section 4: FIRST AID MEASURES**

#### Inhalation

Remove to fresh air. If symptoms persist, call a physician.

#### Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

## Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

#### Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

## Protection of first-aiders

Use personal protective equipment as required.

## Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Water spray (fog), Carbon dioxide (CO2), Foam, Extinguishing powder, Sand

#### Unsuitable extinguishing media

No information available

#### Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

#### Special extinguishing method

No information available

#### Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

#### Section 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

#### **Environmental precautions**

To be careful not discharged to the environment without being properly handled waste water contaminated.

## Methods and materials for contaminent and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

## Recoverly, neutralization

No information available

#### Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

## Section 7: HANDLING AND STORAGE

#### Handling

#### **Technical measures**

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

#### **Precautions**

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging. Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle. In places other than those specified, should not be smoking or eating and drinking. Should not be brought contaminated protective equipment and gloves to rest stops. Deny unnecessary entry of non-emergency personnel to the handling area.

#### Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

#### **Storage**

Safe storage conditions

Storage conditions Keep container protect from light, store

in well-ventilated place at room temperature (preferably cool). Keep container tightly

closed.

Safe packaging material Glass

Incompatible substances Strong oxidizing agents

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Engineering controls**

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and handand eye-wash facility. And display their position clearly.

#### **Exposure limits**

	Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
Π	2-Ethoxyethanol	TWA: 5 ppm OEL	ISHL/ACL: 5 ppm	TWA: 5 ppm

110-80-5	TWA: 18 mg/m <sup>3</sup> OEL	Skin
	Skin	
	ISHL/ACL: 5 ppm	

Personal protective equipment

Respiratory protection gas mask for organic gas (JIS T 8152) chemical protective gloves (JIS T 8116) Hand protection

Eye protection protective eyeglasses or chemical safety goggles (JIS T 8147)

Long-sleeved work clothes Skin and body protection

**General hygiene considerations** 

Handle in accordance with good industrial hygiene and safety practice.

If this product is classified as "Chemical Substances Hazardous to Skin, etc.", use appropriate protective equipment to

them.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form

Color blue **Appearance** liquid

characteristic odor Odor

Melting point/freezing point -70 °C Boiling point, initial boiling point and boiling range 135 °C

Flammable liquid and vapor **Flammability** 

no data available **Evaporation rate:** Flammability (solid, gas): no data available

Upper/lower flammability or explosive limits

15.7 % Upper: Lower: 2.6 %

Flash point 42 °C / 108 °F 235 °C / 455 °F **Auto-ignition temperature: Decomposition temperature:** no data available no data available Viscosity (coefficient of viscosity) no data available

**Dynamic viscosity** no data available Solubilities water: Very soluble.

n-Octanol/water partition coefficient:(log Pow) -0.540

no data available Vapour pressure

Specific Gravity / Relative density 0.931 Vapour density 3.1 (air = 1)**Particle characteristics** no data available

## **Section 10: STABILITY AND REACTIVITY**

## **Stability**

Reactivity no data available Chemical stability May be altered by light.

Hazardous reactions

None under normal processing

**Conditions to avoid** 

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Carbon monooxide (CO), Carbon dioxide (CO2)

## **Section 11: TOXICOLOGICAL INFORMATION**

-							
Δ		ı ıt	Δ	+1	۱V	$\sim$ 1	tν
_	·	uι	ᢏ	···	N	u	ιv

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Ethoxyethanol	2125 - 5720 mg/kg (rat)	3900 mg/kg (rat)	4119 ppm (rat) 4 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas- source information
2-Ethoxyethanol	Based on the NITE GHS	Based on the NITE GHS	Based on the NITE GHS
	classification results.	classification results.	classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust- source information	Acute toxicity -inhalation mist- source information
2-Ethoxyethanol	Based on the NITE GHS	Based on the NITE GHS	Based on the NITE GHS
,	Classification results.	classification results.	classification results.

## Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information	
2-Ethoxyethanol	Based on the NITE GHS classification results.	
Saviana and demand imitation		

#### Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
2-Ethoxyethanol	Based on the NITE GHS classification results.

## Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
2-Ethoxyethanol	Based on the NITE GHS classification results.
	-

## Reproductive cell mutagenicity

Chemical Name	germ cell mutagencity source information
2-Ethoxyethanol	Based on the NITE GHS classification results.

#### Carcinogenicity

Chemical Name	Carcinogenicity source information
2-Ethoxyethanol	Based on the NITE GHS classification results.

## Reproductive toxicity

2 Ethoxy othonol Based on the NITE CHS classification results	Chemical Name	Reproductive toxicity source information	
2-Ethoxyethanol Based on the NITE GITS classification results.	2-Ethoxyethanol	Based on the NITE GHS classification results.	

## STOT-single exposure

Chemical Name	STOT -single exposure- source information
2-Ethoxyethanol	Based on the NITE GHS classification results.
amounted assumptions	

# STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information	
2-Ethoxyethanol	Based on the NITE GHS classification results.	

#### **Aspiration hazard**

Chemical Name	Aspiration Hazard source information
2-Ethoxyethanol	Based on the NITE GHS classification results.

# **Section 12: ECOLOGICAL INFORMATION**

## **Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Ethoxyethanol	EC50:Pseudokirchneriella subcapitata > 100 mg/L 72 h	LC50:Killifish > 94.7 mg/L 96 h	EC50:Daphnia magna 89.5 mg/L 48 h

## Other data

Chemical Name	Short-term (acute) hazardous to the	Long-term (chronic) hazardous to the	
	aquatic environment source information	aquatic environment source information	
2-Ethoxyethanol	Based on the NITE GHS classification	Based on the NITE GHS classification	
	results.	results.	

Persistence and degradability **Bioaccumulative potential** 

Mobility in soil

Hazard to the ozone layer

No information available No information available No information available No information available

## Section 13: DISPOSAL CONSIDERATIONS

#### Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### Section 14: TRANSPORT INFORMATION

ADR/RID

**UN** number UN1171

Ethylene glycol monoethyl ether Proper shipping name:

**UN classfication** 

Subsidiary hazard class

Packing group

Marine pollutant Not applicable

**IMDG** 

**UN** number UN1171

Proper shipping name: Ethylene glycol monoethyl ether

**UN classfication** 

Subsidiary hazard class

Packing group

Marine pollutant (Sea) Not applicable

No information available Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

ΙΔΤΔ

**UN** number UN1171

Proper shipping name: Ethylene glycol monoethyl ether

**UN classfication** 

Subsidiary hazard class

Packing group

**Environmentally Hazardous** Not applicable

Substance

## Section 15: REGULATORY INFORMATION

Japanese regulations

**Fire Service Act** Category IV, Class II petroleums, dangerous grade 3 water-soluble

**Poisonous and Deleterious** 

**Substances Control Law** 

Industrial Safety and Health Act Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57)

Notifiable Substances (Law Art.57-2)

Class 2 Organic Solvents (Enforcement Order Attached Table No.6-2, Ordinance on

Prevention of Organic Solvent Poisoning Art.1, Para.1, Item 5)

Working Environment Evaluation Standards, Administrative Control Levels (Law Art.65-2,

Para.1)

Not applicable

Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1

Item 4)

Industrial Safety and Health Act (

2024~)

【2024.4.1~】Chemical Substances Hazardous to Skin, etc.(Regulations Article 594-2 Paragraph 1)

Regulations for the carriage Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding and storage of dangerous

goods in ship

Transport by Ship and Storage, Attached Table 1)

**Civil Aeronautics Law** 

Flammable Liquids (Ordinance Art.194, MITL Nortification for Air Transportation of

Explosives etc., Attached Table 1)

Pollutant Release and Transfer Class 1

**Register Law** (2023.4.1-)

Class 1 - No.

**Export Trade Control Order** Not applicable

**Air Pollution Control Law** Hazardous Air Pollutants

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2)	Pollutant Release and Transfer Register Law (2023.4.1-)
2-Ethoxyethanol 110-80-5 ( <100 )	-	Applicable	Applicable

## **Section 16: OTHER INFORMATION**

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)

http://www.safe.nite.go.jp/japan/db.html IATA dangerous Goods Regulations

RTECS:Registry of Toxic Effects of Chemical Substances Japan Industrial Safety and Health Association GHS Model SDS

Dictionary of Synthetic Oraganic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.

Chemical Dictionary, Kyouritsu Publishing Co., Ltd.

etc

**Record of SDS revisions Disclaimer** 

The following contents were revised. Regulatory information.

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z 7252:2019. \*JIS: Japanese Industrial Standards

**End of Safety Data Sheet**