

SAFETY DATA SHEET

According to JIS Z 7253:2019
Revision date 21-May-2023
 Revision Number 4.07

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	Xylene
Product Code	249-00097,241-00091,241-00096

Manufacturer FUJIFILM Wako Pure Chemical Corporation
 1-2 Doshomachi 3-Chome
 Chuo-ku, Osaka 540-8605, Japan
 Phone: +81-6-6203-3741
 Fax: +81-6-6203-5964

Supplier FUJIFILM Wako Pure Chemical Corporation
 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan
 Phone: +81-6-6203-3741
 Fax: +81-6-6203-2029

Emergency telephone number +81-6-6203-3741 / +81-3-3270-8571

Recommended uses For research use only

Restrictions on use Seek expert judgment when using for purposes other than those recommended.

Section 2: HAZARDS IDENTIFICATION

GHS classification

Classification of the substance or mixture

Flammable liquids	Category 3
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1, Category 3
Category 1 central nervous system, respiratory system, liver, kidneys	
Category 3 Narcotic effects	
Specific target organ toxicity (repeated exposure)	Category 1
Category 1 nervous system, respiratory system	
Aspiration hazard	Category 1
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

Pictograms



Signal word

Danger

Hazard statements

- H226 - Flammable liquid and vapour
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H312 - Harmful in contact with skin
- H332 - Harmful if inhaled

H360 - May damage fertility or the unborn child
 H336 - May cause drowsiness or dizziness
 H304 - May be fatal if swallowed and enters airways
 H411 - Toxic to aquatic life with long lasting effects
 H401 - Toxic to aquatic life
 H370 - Causes damage to the following organs: central nervous system, respiratory system, liver, kidneys
 H372 - Causes damage to the following organs through prolonged or repeated exposure: nervous system, respiratory system

Precautionary statements-(Prevention)

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Do not breathe dust/fume/gas/mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary statements-(Response)

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- Call a POISON CENTER or doctor/physician if you feel unwell
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting
- In case of fire: Use CO₂, dry chemical, or foam for extinction
- Collect spillage

Precautionary statements-(Storage)

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up

Precautionary statements-(Disposal)

- Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Substance

Formula C₆H₄(CH₃)₂

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
Xylene	>80	106.17	(3)-3, (3)-60	*	1330-20-7
Ethylbenzene	<20	106.17	(3)-28,(3)-60	*	100-41-4

Note on ISHL No.: * in the table means announced chemical substances.

Impurities and/or Additives: Not applicable

Substances Remarks: This product is composed of isomer mixture.

Section 4: FIRST AID MEASURES

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog), Carbon dioxide (CO₂), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

Special extinguishing method

No information available

Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminant and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recovery, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling**Technical measures**

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and

then gargle In places other than those specified, should not be smoking or eating and drinking Should not be brought contaminated protective equipment and gloves to rest stops Deny unnecessary entry of non-emergency personnel to the handling area

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Storage**Safe storage conditions****Storage conditions**

Store away from sunlight in well-ventilated place at room temperature (preferably cool).
Keep container tightly closed. Store locked up.

Safe packaging material

Glass, Iron

Incompatible substances

Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

Exposure limits

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
Xylene 1330-20-7	TWA: 50 ppm OEL TWA: 217 mg/m ³ OEL ISHL/ACL: 50 ppm	ISHL/ACL: 50 ppm	STEL: 150 ppm TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 50 ppm OEL TWA: 217 mg/m ³ OEL ISHL/ACL: 20 ppm	ISHL/ACL: 20 ppm	TWA: 20 ppm

Personal protective equipment**Respiratory protection**

gas mask for organic gas (JIS T 8152)

Hand protection

chemical protective gloves (JIS T 8116)

Eye protection

protective eyeglasses or chemical safety goggles

Skin and body protection

Long-sleeved work clothes, protective boots

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form**Color**

colorless

Turbidity

clear

Appearance

liquid

Odor

characteristic odor

Melting point/freezing point

-50 °C

Boiling point, initial boiling point and boiling range

140 °C

Flammability

Flammable liquid and vapor

Evaporation rate:

no data available

Flammability (solid, gas):

no data available

Upper/lower flammability or explosive limits**Upper:**

7 vol%

Lower:

1 vol%

Flash point

25 °C

Auto-ignition temperature:

no data available

Decomposition temperature:

no data available

pH

no data available

Viscosity (coefficient of viscosity)

no data available

Dynamic viscosity

no data available

Solubilities

Ethanol and Diethyl ether : Very soluble. water : practically insoluble,or insoluble .

n-Octanol/water partition coefficient:(log Pow)

no data available

Vapour pressure	no data available
Specific Gravity / Relative density	0.860 - 0.870 g/mL
Vapour density	3.7
Particle characteristics	no data available

Section 10: STABILITY AND REACTIVITY

Stability

Reactivity	no data available
Chemical stability	Stable under recommended storage conditions.
Hazardous reactions	None under normal processing
Conditions to avoid	Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	Carbon monoxide (CO), Carbon dioxide (CO ₂)

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	3500 - 8800 mg/kg (Rat)	1700 mg/kg (Rabbit)	6350 - 6700 ppm (Rat) 4 h
Ethylbenzene	3500 - 4700 mg/kg (Rat)	15400 mg/kg (Rabbit)	4000 ppm (Rat) 4 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas-source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust-source information	Acute toxicity -inhalation mist-source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Carcinogenicity

Chemical Name	Carcinogenicity source information
Xylene	Based on the NITE GHS classification results.

Ethylbenzene	Based on the NITE GHS classification results.
--------------	---

Chemical Name	NTP	IARC	ACGIH	JSOH (Japan)
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	-	Group 2B	A3	Group 2B

Reproductive toxicity

Chemical Name	Reproductive toxicity source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

STOT-single exposure

Chemical Name	STOT -single exposure- source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Aspiration hazard

Chemical Name	Aspiration Hazard source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene	N/A	LC50 : <i>Oncorhynchus mykiss</i> 3.3 mg/L	N/A
Ethylbenzene	N/A	LC50 : <i>Morone saxatilis</i> 3.7 mg/L 96 h	LC50 : <i>Crangon crangon</i> 0.42 mg/L 96 h

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Persistence and degradability	No information available
Bioaccumulative potential	No information available
Mobility in soil	No information available
Hazard to the ozone layer	No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

ADR/RID

UN number UN1307

Proper shipping name: Xylenes
UN classification 3
Subsidiary hazard class
Packing group III
Marine pollutant Yes

IMDG

UN number UN1307
Proper shipping name: Xylenes
UN classification 3
Subsidiary hazard class
Packing group III
Marine pollutant (Sea) Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

IATA

UN number UN1307
Proper shipping name: Xylenes
UN classification 3
Subsidiary hazard class
Packing group III
Environmentally Hazardous Substance Yes

Section 15: REGULATORY INFORMATION**International Inventories**

EINECS/ELINCS Listed
TSCA Listed

Japanese regulations

Fire Service Act Category IV, Class II petroleums, dangerous grade 3
Poisonous and Deleterious Substances Control Law Deleterious Substances 3rd. Grade
Industrial Safety and Health Act Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18)
 Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)No.70,136
 Class 2 Organic Solvents (Enforcement Order Attached Table No.6-2, Ordinance on Prevention of Organic Solvent Poisoning Art.1, Para.1, Item 5)
 Group 2 Specified Chemical Substance
 Substances with Health Hazards Prevention Guideline(Carcinogenicity Substance)
 Working Environment Evaluation Standards, Administrative Control Levels (Law Art.65-2, Para.1)
 Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1 Item 4)
Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc Priority Assessment Chemical Substances (Law Article 2, Para.5)
Regulations for the carriage and storage of dangerous goods in ship Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
Civil Aeronautics Law Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
Marine Pollution Prevention Law Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y
Pollutant Release and Transfer Register Law Dangerous Substances
(2023.4.1-) Class 1
Class 1 - No. 53,80
Water Pollution Control Act Specified substances(Law Art.2 Para.4, Enforcement Order Art.3-3)

Export Trade Control Order Not applicable
Air Pollution Control Law Hazardous Air Pollutants
Offensive Odor Control Law Specified Offensive Odor Substances

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2) (~2024.3.31)	Pollutant Release and Transfer Register Law (2023.4.1-)
Xylene 1330-20-7 (>80)	Applicable	Applicable	Applicable
Ethylbenzene 100-41-4 (<20)	-	Applicable	Applicable

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)
<http://www.safe.nite.go.jp/japan/db.html>
 IATA dangerous Goods Regulations
 RTECS:Registry of Toxic Effects of Chemical Substances
 Japan Industrial Safety and Health Association GHS Model SDS
 Dictionary of Synthetic Organic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.
 Chemical Dictionary, Kyouritsu Publishing Co., Ltd.
 etc

Record of SDS revisions

The following contents were revised. Product and company Identification. Exposure controls/personal protection. Regulatory information.

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z 7252:2019. *JIS: Japanese Industrial Standards

End of Safety Data Sheet