

SAFETY DATA SHEET

According to JIS Z 7253:2019
Revision date 27-Feb-2024
 Revision Number 2.03

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	Xylene Standard Solution (o-,m-,p- each 1mg/mL Methanol Solution)
Product Code	245-00631

Supplier	FUJIFILM Wako Pure Chemical Corporation 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan Phone: +81-6-6203-3741 Fax: +81-6-6203-2029
Emergency telephone number	+81-6-6203-3741 / +81-3-3270-8571
Recommended uses	For research use only
Restrictions on use	Seek expert judgment when using for purposes other than those recommended.

Section 2: HAZARDS IDENTIFICATION

GHS classification**Classification of the substance or mixture**

Flammable liquids

Category 2

Acute toxicity - Oral

Category 4

Serious eye damage/eye irritation

Category 2A

Reproductive Toxicity

Category 1B

Specific target organ toxicity (single exposure)

Category 1, Category 3

Category 1 central nervous system, Visual organ, systemic toxicity

Category 3 Narcotic effects

Specific target organ toxicity (repeated exposure)

Category 1

Category 1 central nervous system, Visual organ

Pictograms

Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H302 - Harmful if swallowed

H360 - May damage fertility or the unborn child

H336 - May cause drowsiness or dizziness

H370 - Causes damage to the following organs: central nervous system, Visual organ, systemic toxicity

H372 - Causes damage to the following organs through prolonged or repeated exposure: central nervous system, Visual organ

Precautionary statements-(Prevention)

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood

- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary statements-(Response)

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth
- In case of fire: Use suitable extinguishing media for extinction

Precautionary statements-(Storage)

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Precautionary statements-(Disposal)

- Dispose of contents/container to an approved waste disposal plant

Others

Other hazards Not available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single Substance or Mixture Mixture

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
Methanol	<100	32.04	(2)-201	*	67-56-1
o-Xylene	0.1	106.17	(3)-3,(3)-60	4-(1)-39	95-47-6
p-Xylene	0.1	106.17	(3)-3,(3)-60	4-(1)-39	106-42-3
m-Xylene	0.1	106.17	(3)-3,(3)-60	4-(1)-39	108-38-3

Note on ISHL No.: * in the table means announced chemical substances.

Section 4: FIRST AID MEASURES

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

Protection of first-aiders

Use personal protective equipment as required.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog), Carbon dioxide (CO₂), Foam, Extinguishing powder, Sand

Unsuitable extinguishing media

No information available

Specific hazards arising from the chemical product

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixture with air

Special extinguishing method

No information available

Special protective actions for fire-fighters

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

Environmental precautions

To be careful not discharged to the environment without being properly handled waste water contaminated.

Methods and materials for contaminant and methods and materials for cleaning up

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

Recovery, neutralization

No information available

Secondary disaster prevention measures

Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: HANDLING AND STORAGE

Handling

Technical measures

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. To cut with care and wear protective gloves and protective goggles to ampoule time of the opening (Cutting method to check the label). Use with local exhaust ventilation.

Precautions

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging. Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and then gargle. In places other than those specified, should not be smoking or eating and drinking. Should not be brought contaminated protective equipment and gloves to rest stops. Deny unnecessary entry of non-emergency personnel to the handling area.

Safety handling precautions

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Storage

Safe storage conditions

Storage conditions

Keep container protect from light tightly closed. Store in a cool (2-10 °C) place.

Safe packaging material

Ampoule

Incompatible substances

Strong oxidizing agents

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

Exposure limits

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
Methanol 67-56-1	TWA: 200 ppm OEL TWA: 260 mg/m ³ OEL Skin ISHL/ACL: 200 ppm	200ppm	TWA 200ppm(260mg/m ³) STEL 250ppm
o-Xylene 95-47-6	TWA: 50 ppm OEL TWA: 217 mg/m ³ OEL ISHL/ACL: 50 ppm	ISHL/ACL: 50 ppm	TWA: 20 ppm
p-Xylene 106-42-3	TWA: 50 ppm OEL TWA: 217 mg/m ³ OEL ISHL/ACL: 50 ppm	ISHL/ACL: 50 ppm	TWA: 20 ppm
m-Xylene 108-38-3	TWA: 50 ppm OEL TWA: 217 mg/m ³ OEL ISHL/ACL: 50 ppm	ISHL/ACL: 50 ppm	TWA: 20 ppm

Personal protective equipment

Respiratory protection	gas mask for organic gas (JIS T 8152)
Hand protection	chemical protective gloves (JIS T 8116)
Eye protection	protective eyeglasses or chemical safety goggles (JIS T 8147)
Skin and body protection	Long-sleeved work clothes

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

If this product is classified as "Chemical Substances Hazardous to Skin, etc.", use appropriate protective equipment to them.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form

Color	colorless
Turbidity	clear
Appearance	liquid
Odor	characteristic odor
Melting point/freezing point	-98 °C
Boiling point, initial boiling point and boiling range	65 °C
Flammability	Highly flammable liquid and vapor
Evaporation rate:	no data available
Flammability (solid, gas):	no data available
Upper/lower flammability or explosive limits	
Upper:	36.5%
Lower:	6.0%
Flash point	11 °C
Auto-ignition temperature:	464 °C
Decomposition temperature:	no data available
pH	no data available
Viscosity (coefficient of viscosity)	no data available
Dynamic viscosity	no data available
Solubilities	water , Ethanol : at the rate of any miscible .
n-Octanol/water partition coefficient:(log Pow)	-0.82
Vapour pressure	123hPa
Specific Gravity / Relative density	0.729
Vapour density	1.1(Air=1)

Particle characteristics

no data available

Section 10: STABILITY AND REACTIVITY

Stability

Reactivity no data available
Chemical stability May be altered by light.

Hazardous reactions

None under normal processing

Conditions to avoid

Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Carbon monoxide (CO), Carbon dioxide (CO₂)

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methanol	1400 mg/kg (Human)	15800 mg/kg (Rabbit)	>31500 ppm (Rat) 4 h (vapor)
o-Xylene	3600 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	4330 ppm (Rat) 6 h
p-Xylene	4029 mg/kg (Rat)	N/A	4550 ppm (Rat) 4 h 4740 ppm (Rat) 4 h
m-Xylene	4320 - 6700 mg/kg (Rat)	3228 - 14100 mg/kg (Rabbit)	5984 ppm (Rat) 6 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas-source information
Methanol	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust-source information	Acute toxicity -inhalation mist-source information
Methanol	Based on the NITE GHS Classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
---------------	--

Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Carcinogenicity

Chemical Name	Carcinogenicity source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Chemical Name	NTP	IARC	ACGIH	JSOH (Japan)
o-Xylene 95-47-6	-	Group 3		-
p-Xylene 106-42-3		Group 3		
m-Xylene 108-38-3	-	Group 3		-

Reproductive toxicity

Chemical Name	Reproductive toxicity source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

STOT-single exposure

Chemical Name	STOT -single exposure- source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

STOT-repeated exposure

Chemical Name	STOT -repeated exposure- source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Aspiration hazard

Chemical Name	Aspiration Hazard source information
Methanol	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methanol	N/A	LC50 : <i>Lepomis macrochirus</i> 15400 mg/L 96 h	LC50 : <i>Artemia</i> 1340 mg/L 96 h
o-Xylene	ErC50 : <i>Scenedesmus</i> sp. 0.799 mg/L 72 h	LC50 : <i>Oncorhynchus mykiss</i> 5.59 - 11.6 mg/L 96 h	EC50 : <i>Daphnia magna</i> 0.78 - 2.51 mg/L 48 h
p-Xylene	EC50: <i>Chlorella vulgaris</i> 105.1 mg/L 3 h EC50: <i>Pseudokirchneriella subcapitata</i> 3.2 mg/L 72 h static	LC50 : <i>Morone saxatilis</i> 1.7 mg/L 96 h	EC50 : <i>Crangon crangon</i> 1.7 mg/L 96 h
m-Xylene	EC50 : <i>Pseudokirchneriella subcapitata</i> 4.9 mg/L 72 h static	LC50 : <i>Pimephales promelas</i> 14.3 - 18 mg/L 96 h LC50 : <i>Poecilia reticulata</i> 12.9 mg/L 96 h LC50 : <i>Oncorhynchus mykiss</i> 8.4 mg/L 96 h	EC50 : <i>Daphnia magna</i> 2.42 mg/L 48 h

Other data

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
Methanol	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
o-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
p-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
m-Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Persistence and degradability	No information available
Bioaccumulative potential	No information available
Mobility in soil	No information available
Hazard to the ozone layer	No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated container and contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

ADR/RID

UN number	UN1230
Proper shipping name:	Methanol
UN classification	3
Subsidiary hazard class	6.1
Packing group	II
Marine pollutant	Not applicable

IMDG

UN number	UN1230
Proper shipping name:	Methanol
UN classification	3

Subsidiary hazard class 6.1
Packing group II
Marine pollutant (Sea) Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

IATA

UN number UN1230
Proper shipping name: Methanol
UN classification 3
Subsidiary hazard class 6.1
Packing group II
Environmentally Hazardous Substance Not applicable

Section 15: REGULATORY INFORMATION

Japanese regulations

Fire Service Act Category IV, alcohols, dangerous grade 2 water-soluble
Poisonous and Deleterious Substances Control Law Not applicable
Industrial Safety and Health Act Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57)
Notifiable Substances (Law Art.57-2)
Class 2 Organic Solvents (Enforcement Order Attached Table No.6-2, Ordinance on Prevention of Organic Solvent Poisoning Art.1, Para.1, Item 5)
Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1 Item 4)
Working Environment Evaluation Standards, Administrative Control Levels (Law Art.65-2, Para.1)
Industrial Safety and Health Act (2024-) **【2024.4.1~】** Chemical Substances Hazardous to Skin, etc.(Regulations Article 594-2 Paragraph 1)
Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc Priority Assessment Chemical Substances (Law Article 2, Para.5)
Regulations for the carriage and storage of dangerous goods in ship Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
Civil Aeronautics Law Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
Marine Pollution Prevention Law Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y
Pollutant Release and Transfer Register Law (2023.4.1-) Dangerous Substances
Water Pollution Control Act Not applicable
Export Trade Control Order Specified substances(Law Art.2 Para.4, Enforcement Order Art.3-3)
Air Pollution Control Law Not applicable
Specified Substances, Volatile Organic Compound, Hazardous Air Pollutants

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2)	Pollutant Release and Transfer Register Law (2023.4.1-)
Methanol 67-56-1 (<100)	-	Applicable	-
o-Xylene 95-47-6 (0.1)	-	Applicable	-
p-Xylene 106-42-3 (0.1)	-	Applicable	-
m-Xylene	-	Applicable	-

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2)	Pollutant Release and Transfer Register Law (2023.4.1-)
108-38-3 (0.1)			

Section 16: OTHER INFORMATION

Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)
<http://www.safe.nite.go.jp/japan/db.html>
IATA dangerous Goods Regulations
RTECS:Registry of Toxic Effects of Chemical Substances
Japan Industrial Safety and Health Association GHS Model SDS
Dictionary of Synthetic Organic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.
Chemical Dictionary, Kyouritsu Publishing Co., Ltd.
etc

Record of SDS revisions

The following contents were revised. Regulatory information.

Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z 7252:2019. *JIS: Japanese Industrial Standards

End of Safety Data Sheet