

# SAFETY DATA SHEET

According to JIS Z 7253:2019  
**Revision date** 21-May-2023  
 Revision Number 5.05

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name</b>	Xylene, Super Dehydrated
<b>Product Code</b>	240-00865,248-00861

**Manufacturer** FUJIFILM Wako Pure Chemical Corporation  
 1-2 Doshomachi 3-Chome  
 Chuo-ku, Osaka 540-8605, Japan  
 Phone: +81-6-6203-3741  
 Fax: +81-6-6203-5964

**Supplier** FUJIFILM Wako Pure Chemical Corporation  
 1-2 Doshomachi 3-Chome, Chuo-ku, Osaka 540-8605, Japan  
 Phone: +81-6-6203-3741  
 Fax: +81-6-6203-2029

**Emergency telephone number** +81-6-6203-3741 / +81-3-3270-8571

**Recommended uses** For research use only

**Restrictions on use** Seek expert judgment when using for purposes other than those recommended.

## Section 2: HAZARDS IDENTIFICATION

**GHS classification**

**Classification of the substance or mixture**

<b>Flammable liquids</b>	Category 3
<b>Acute toxicity - Dermal</b>	Category 4
<b>Acute toxicity - Inhalation (Vapors)</b>	Category 4
<b>Skin corrosion/irritation</b>	Category 2
<b>Serious eye damage/eye irritation</b>	Category 2A
<b>Reproductive Toxicity</b>	Category 1B
<b>Specific target organ toxicity (single exposure)</b>	Category 1, Category 3
<b>Category 1</b> central nervous system, respiratory system, liver, kidneys	
<b>Category 3</b> Narcotic effects	
<b>Specific target organ toxicity (repeated exposure)</b>	Category 1
<b>Category 1</b> nervous system, respiratory system	
<b>Aspiration hazard</b>	Category 1
<b>Acute aquatic toxicity</b>	Category 2
<b>Chronic aquatic toxicity</b>	Category 2

**Pictograms**



**Signal word**

Danger

**Hazard statements**

- H226 - Flammable liquid and vapour
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H312 - Harmful in contact with skin
- H332 - Harmful if inhaled

H360 - May damage fertility or the unborn child  
 H336 - May cause drowsiness or dizziness  
 H304 - May be fatal if swallowed and enters airways  
 H411 - Toxic to aquatic life with long lasting effects  
 H401 - Toxic to aquatic life  
 H370 - Causes damage to the following organs: central nervous system, respiratory system, liver, kidneys  
 H372 - Causes damage to the following organs through prolonged or repeated exposure: nervous system, respiratory system

**Precautionary statements-(Prevention)**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Do not breathe dust/fume/gas/mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating / lighting / equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Precautionary statements-(Response)**

- IF exposed: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- Call a POISON CENTER or doctor/physician if you feel unwell
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting
- In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction
- Collect spillage

**Precautionary statements-(Storage)**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up

**Precautionary statements-(Disposal)**

- Dispose of contents/container to an approved waste disposal plant

**Others**

**Other hazards** Not available

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**Single Substance or Mixture** Substance

**Formula** C<sub>6</sub>H<sub>4</sub>(CH<sub>3</sub>)<sub>2</sub>

Chemical Name	Weight-%	Molecular weight	ENCS	ISHL No.	CAS RN
Xylene	>80	106.17	(3)-3, (3)-60	*	1330-20-7
Ethylbenzene	<20	106.17	(3)-28,(3)-60	*	100-41-4

**Note on ISHL No.:** \* in the table means announced chemical substances.

**Impurities and/or Additives:** Not applicable

**Substances Remarks:** This product is composed of isomer mixture.

---

## Section 4: FIRST AID MEASURES

**Inhalation**

Remove to fresh air. If symptoms persist, call a physician.

**Skin contact**

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

**Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

**Ingestion**

Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Do not induce vomiting without medical advice.

**Protection of first-aiders**

Use personal protective equipment as required.

## Section 5: FIRE FIGHTING MEASURES

**Suitable extinguishing media**

Water spray (fog), Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder, Sand

**Unsuitable extinguishing media**

No information available

**Specific hazards arising from the chemical product**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may form explosive mixtures with air

**Special extinguishing method**

No information available

**Special protective actions for fire-fighters**

Use personal protective equipment as required. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

For indoor, provide adequate ventilation process until the end of working. Deny unnecessary entry other than the people involved by, for example, using a rope. While working, wear appropriate protective equipments to avoid adhering it on skin, or inhaling the gas. Work from windward, and retract the people downwind.

**Environmental precautions**

To be careful not discharged to the environment without being properly handled waste water contaminated.

**Methods and materials for contaminant and methods and materials for cleaning up**

Absorb dry sand, earth, sawdust and the waste. Collect empty container that can be sealed.

**Recovery, neutralization**

No information available

**Secondary disaster prevention measures**

Clean contaminated objects and areas thoroughly observing environmental regulations.

## Section 7: HANDLING AND STORAGE

**Handling****Technical measures**

Highly flammable. Avoid contact with high temperature objects, spark, and strong oxidizing agents. Use with local exhaust ventilation.

**Precautions**

Do not rough handling containers, such as upsetting, falling, giving a shock, and dragging Prevent leakage, overflow, and scattering. Not to generate steam and dust in vain. Seal the container after use. After handling, wash hands and face, and

then gargle In places other than those specified, should not be smoking or eating and drinking Should not be brought contaminated protective equipment and gloves to rest stops Deny unnecessary entry of non-emergency personnel to the handling area

**Safety handling precautions**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**Storage****Safe storage conditions****Storage conditions**

Keep container protect from light, store in well-ventilated place at room temperature (preferably cool). Keep container tightly closed. Packed with an inert gas. Store locked up.

**Safe packaging material**

Glass

**Incompatible substances**

Strong oxidizing agents

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls**

In case of indoor workplace, seal the source or use a local exhaust system. Provide the safety shower facility, and hand- and eye-wash facility. And display their position clearly.

**Exposure limits**

Chemical Name	JSOH (Japan)	ISHL (Japan)	ACGIH
Xylene 1330-20-7	TWA: 50 ppm OEL TWA: 217 mg/m <sup>3</sup> OEL ISHL/ACL: 50 ppm	ISHL/ACL: 50 ppm	STEL: 150 ppm TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 50 ppm OEL TWA: 217 mg/m <sup>3</sup> OEL ISHL/ACL: 20 ppm	ISHL/ACL: 20 ppm	TWA: 20 ppm

**Personal protective equipment****Respiratory protection**

gas mask for organic gas ( JIS T 8152 )

**Hand protection**

chemical protective gloves ( JIS T 8116 )

**Eye protection**

protective eyeglasses or chemical safety goggles

**Skin and body protection**

Long-sleeved work clothes

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Form****Color**

colorless

**Turbidity**

clear

**Appearance**

liquid

**Odor**

characteristic odor

**Melting point/freezing point**

-50 °C

**Boiling point, initial boiling point and boiling range**

140 °C

**Flammability**

Flammable liquid and vapor

**Evaporation rate:**

no data available

**Flammability (solid, gas):**

no data available

**Upper/lower flammability or explosive limits****Upper:**

7 vol%

**Lower:**

1 vol%

**Flash point**

25 °C

**Auto-ignition temperature:**

no data available

**Decomposition temperature:**

no data available

**pH**

no data available

**Viscosity (coefficient of viscosity)**

no data available

**Dynamic viscosity**

no data available

**Solubilities**

Ethanol : Very soluble. water : practically insoluble,or insoluble

n-Octanol/water partition coefficient:(log Pow)	no data available
Vapour pressure	no data available
Specific Gravity / Relative density	0.87 g/mL
Vapour density	3.7
Particle characteristics	no data available

## Section 10: STABILITY AND REACTIVITY

### Stability

<b>Reactivity</b>	no data available
<b>Chemical stability</b>	May be altered by light.
<b>Hazardous reactions</b>	None under normal processing
<b>Conditions to avoid</b>	Extremes of temperature and direct sunlight, Heat, flames and sparks, static electricity, spark
<b>Incompatible materials</b>	Strong oxidizing agents
<b>Hazardous decomposition products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )

## Section 11: TOXICOLOGICAL INFORMATION

### Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	3500 - 8800 mg/kg ( Rat )	1700 mg/kg ( Rabbit )	6350 - 6700 ppm ( Rat ) 4 h
Ethylbenzene	3500 - 4700 mg/kg ( Rat )	15400 mg/kg ( Rabbit )	4000 ppm ( Rat ) 4 h

Chemical Name	Acute toxicity -oral- source information	Acute toxicity -dermal- source information	Acute toxicity -inhalation gas-source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

Chemical Name	Acute toxicity -inhalation vapor- source information	Acute toxicity -inhalation dust-source information	Acute toxicity -inhalation mist-source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

### Skin irritation/corrosion

Chemical Name	Skin corrosion/irritation source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

### Serious eye damage/ irritation

Chemical Name	Serious eye damage/irritation source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

### Respiratory or skin sensitization

Chemical Name	Respiratory or Skin sensitization source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

### Reproductive cell mutagenicity

Chemical Name	germ cell mutagenicity source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

### Carcinogenicity

Chemical Name	Carcinogenicity source information
---------------	------------------------------------

Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

Chemical Name	NTP	IARC	ACGIH	JSOH (Japan)
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	-	Group 2B	A3	Group 2B

**Reproductive toxicity**

Chemical Name	Reproductive toxicity source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

**STOT-single exposure**

Chemical Name	STOT -single exposure- source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

**STOT-repeated exposure**

Chemical Name	STOT -repeated exposure- source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

**Aspiration hazard**

Chemical Name	Aspiration Hazard source information
Xylene	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene	N/A	LC50 : <i>Oncorhynchus mykiss</i> 3.3 mg/L	N/A
Ethylbenzene	N/A	LC50 : <i>Morone saxatilis</i> 3.7 mg/L 96 h	LC50 : <i>Crangon crangon</i> 0.42 mg/L 96 h

**Other data**

Chemical Name	Short-term (acute) hazardous to the aquatic environment source information	Long-term (chronic) hazardous to the aquatic environment source information
Xylene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.
Ethylbenzene	Based on the NITE GHS classification results.	Based on the NITE GHS classification results.

<b>Persistence and degradability</b>	No information available
<b>Bioaccumulative potential</b>	No information available
<b>Mobility in soil</b>	No information available
<b>Hazard to the ozone layer</b>	No information available

## Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated container and contaminated packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14: TRANSPORT INFORMATION

**ADR/RID**

UN number	UN1307
Proper shipping name:	Xylenes
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant	Yes

**IMDG**

UN number	UN1307
Proper shipping name:	Xylenes
UN classification	3
Subsidiary hazard class	
Packing group	III
Marine pollutant (Sea)	Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

**IATA**

UN number	UN1307
Proper shipping name:	Xylenes
UN classification	3
Subsidiary hazard class	
Packing group	III
Environmentally Hazardous Substance	Yes

<b>Section 15: REGULATORY INFORMATION</b>
---

**International Inventories**

EINECS/ELINCS	Listed
TSCA	Listed

**Japanese regulations**

<b>Fire Service Act</b>	Category IV, Class II petroleums, dangerous grade 3
<b>Poisonous and Deleterious Substances Control Law</b>	Deleterious Substances 3rd. Grade
<b>Industrial Safety and Health Act</b>	Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18) Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)No.70,136 Class 2 Organic Solvents (Enforcement Order Attached Table No.6-2, Ordinance on Prevention of Organic Solvent Poisoning Art.1, Para.1, Item 5) Group 2 Specified Chemical Substance Substances with Health Hazards Prevention Guideline(Carcinogenicity Substance) Working Environment Evaluation Standards, Administrative Control Levels (Law Art.65-2, Para.1) Dangerous Substances - Flammable Substance (Enforcement Order Attached Table 1 Item 4) Priority Assessment Chemical Substances (Law Article 2, Para.5)
<b>Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc</b>	
<b>Regulations for the carriage and storage of dangerous goods in ship</b>	Flammable Liquids (Ordinance Art.3, Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Attached Table 1)
<b>Civil Aeronautics Law</b>	Flammable Liquids (Ordinance Art.194, MITL Notification for Air Transportation of Explosives etc., Attached Table 1)
<b>Marine Pollution Prevention Law</b>	Enforcement ordinance Appendix No. 1 Noxious liquid substance Category Y Dangerous Substances
<b>Pollutant Release and Transfer Register Law (2023.4.1-)</b>	Class 1
<b>Class 1 - No.</b>	53,80

<b>Water Pollution Control Act</b>	Specified substances(Law Art.2 Para.4, Enforcement Order Art.3-3)
<b>Export Trade Control Order</b>	Not applicable
<b>Air Pollution Control Law</b>	Hazardous Air Pollutants
<b>Offensive Odor Control Law</b>	Specified Offensive Odor Substances

Chemical Name	Poisonous and Deleterious Substances Control Law	Industrial Safety and Health Act Substances (Law Art.57-2) (~2024.3.31)	Pollutant Release and Transfer Register Law (2023.4.1-)
Xylene 1330-20-7 ( >80 )	Applicable	Applicable	Applicable
Ethylbenzene 100-41-4 ( <20 )	-	Applicable	Applicable

## Section 16: OTHER INFORMATION

### Key literature references and sources for data etc.

NITE: National Institute of Technology and Evaluation (JAPAN)  
<http://www.safe.nite.go.jp/japan/db.html>  
 IATA dangerous Goods Regulations  
 RTECS:Registry of Toxic Effects of Chemical Substances  
 Japan Industrial Safety and Health Association GHS Model SDS  
 Dictionary of Synthetic Organic Chemistry , SSOCJ, Koudansha Scientific Co.Ltd.  
 Chemical Dictionary, Kyouritsu Publishing Co., Ltd.  
 etc

### Record of SDS revisions

The following contents were revised. Product and company Identification. Exposure controls/personal protection. Regulatory information.

### Disclaimer

This SDS is according to JIS Z 7253: 2019. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GHS Classification is according to JIS Z 7252:2019. \*JIS: Japanese Industrial Standards

**End of Safety Data Sheet**